

AC30

10 MIL MEDIUM GRADE DUCT TAPE

DESCRIPTION

Polyethylene (PE) coated cloth tape with an aggressive pressure sensitive natural rubber adhesive. Designed to answer the end-use/consumer need for an economical general purpose duct tape.

PRODUCT APPLICATION

Packaging, wrapping and sealing, binding and bundling, exterminators, book repair, weather proofing, and general maintenance.

GOVERNMENT COMPLIANCE

Tested in accordance with UL-723.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	PE coated cloth
Adhesive	Natural Rubber/Resin
Tensile Strength (lbs/in of width) PSTC-131	20 (87.5 N/25mm)
Elongation (% at break)	18
Adhesion to Steel (oz/in of width) PSTC-101	55 (15 N/25mm)
Quick Stick to Steel (oz/in of width) PSTC-105	26 (7 N/25mm)
Total Thickness (mils) PSTC-133	10 (0.254mm)
Colors	Silver, Black, Red



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/11

