

# STANDARD DUTY COMBO SHRINK SYSTEM

MODEL: HSE100



## FEATURES

### CONTROL PANEL

- Express Control Panel for Machine Operations
- Single Plug 115V Power Supply

### SEALING AREA

- Impulse Wire Seal System
- Large 16" W by 20" L Seal Area
- Standard Seal Head with Film Clamps
- Adjustable Height Sealing Platform
- Balanced Magnetic Hold Down
- Pre-Wired Seal Conveyor Ready

### SHRINK TUNNEL

- Independent Tunnel Temperature Control
- Non-Stick Mesh Tunnel Belt
- Automatic Cool Down Extends Heating Element Life



Model HSE100 shown with Leg Kit

### OTHER FEATURES

- One Year Warranty
- **RAPID HS** - Standard Machine Options Ship in 5 Days
- Four Individually Adjustable Perforating Wheels
- Adjustable Film Cradle

## MODEL SPECS

<b>FILM CAPACITY</b>	17" Wide (43 cm)
<b>L BAR SEALING AREA</b>	16" W, 20" L (41 W, 51 L cm)
<b>INSIDE TUNNEL DIMENSIONS</b>	20" L, 14" W, 6.5" H (51 L, 36 W, 17 H cm)
<b>TUNNEL CONVEYOR SPEED</b>	0-20 Feet per Minute (0-6 meters per minute)
<b>OVERALL DIMENSIONS</b>	76.5" L, 24" W, 32"/55" H (Table Top/Leg Kit) (195 L, 61 W, 82 H cm)
<b>WORKING HEIGHT</b>	36" (92 cm) - with Leg Kit
<b>POWER REQUIREMENTS</b>	115 Volts, 17 Amp
<b>WEIGHT</b>	380 LBS
<b>TUNNEL WATTAGE</b>	2,200

## AVAILABLE OPTIONS

- HSE100 with Seal Conveyor and Leg Kit with Casters
- HSE100 with Leg Kit with Casters
- HSE100 Table Top System
- AT36- 36" Rotary Accumulator Table

